



Hi5-Plus

Bring HDMI and 3G-SDI devices together for a full range of monitoring and recording solutions in the edit suite, on set or at live events. Convenient USB setup using AJA MiniConfig on Mac or PC for easy remote configuration.

\$525 US MSRP

<https://www.aja.com/products/hi5-plus>

Video Formats

- (2K) 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (2K) 1080PsF* 23.98, 24, 25, 29.97, 30
- (HD) 1080i 50, 59.94, 60
- (HD) 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (HD) 1080PsF* 23.98, 24, 25, 29.97, 30
- (HD) 720p 50, 59.94, 60
- (SD) 625i
- (SD) 525i

*Converts to progressive

Video Input

- 3G-SDI with embedded audio

Video Outputs

- HDMI with embedded audio up to 8-channels (selectable by Mini-Config)
 - 8-bit RGB 4:4:4
 - 10-bit YCbCr 4:2:2
 - 12-bit

Audio Input

- SDI embedded audio, select from 16-channels

Audio Output

- 2-channel RCA style (-10dBu nominal)

Size (w x d x h)

- 4.6" x 2.4" x 1.0" (117 x 61 x 25mm)

Weight

- 0.3 lb (0.2 kg)

Power

- Universal power supply included
- 100-240V, 50/60 Hz universal input
- +5V DC regulated, 7.5 watt capacity

Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)